



C	芯片型号Sensor Type	2/3"	MAX Image Circle (2y=11.2)
	分辨率Resolution Ratio	5um	Image Space
	机械后焦Flange Distance	17.526mm±0.05mm	In Air
	接口Mount	C	-
	焦距EFL	43.4mm±5%	-
	倍率Magnification	2.0X±5%	-
D	工作距离Work Distance	65mm±3mm	-
	共轭距离Conjugate Distance	166.0mm±5mm	-
	工作光圈WFNO	13.2±5%	At Work Distance
	远心度Telecentricity	0.1°±5%	Object Space
	景深DOF	0.13mm±5%	At F13.2
E	光学畸变Optical Distortion	0.03%±5%	At 2y=11.2
	相对照度Relative Illumination	98.8%±5%	At 2y=11.2

线性尺寸公差	>0.5-6	±0.05	角度尺寸公差	>0-10	±1°	材料
	>6-30	±0.1		>10-50	±30'	
	>30-120	±0.15		>50-120	±20'	
	>120-400	±0.2		>120-400	±10'	



名称
TC200065A_外形规格图

图号

设计	审核	批准			
Y J					
'21.01.04					
图样标记	单位	比例	数量	页码	
	mm	1:1	1	1/1	
标记	处数	位置分区	变更号	签字	日期



描图

旧底图登记号

底图登记号

标记